

TECHNICAL DATA SHEET

Type no.		DA 70	
Article no.		013570290801	
Standards		DIN EN 50342-1,50342-2	
Application		Starter battery	
Electrical data			
Rated voltage		12V	
Rated capacity		70 Ah (K20)	
Cold start current		570 A (EN)	
Dimensions and weights			
Box	D26		
Length max.	260mm		
Width max.	174mm		
Box height max.	200mm		
Total height max.	222mm		
Battery weight	Ca. 17,5 kg (+/- 5 %)	Symbolpicture	
Electrolyte density	Approx. 1,28 kg/l		
Electrolyte	Diluted sulphuric acid		
Items/pallet	51		
Pallet ID	Euro pallet		
Items per layer	17		
Features			
Base hold-down	B1		
Layout	0		
Terminal	1		
Separator	PE bag separator		
Degassing	Battery with central degassing		
Flame arrester	Available		
Maintenance ¹⁾			
Water consumption	< 1g/Ah		
Refill water	Distilled or demineralised (DIN 43530)		
Self-discharge	Approx. 3 % per month		
Charging current	Approx. 1/10 of the rated capacity		
Charging voltage ²⁾	max. 14.8 V		



Symbolpicture

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge

