


TECHNICAL DATA SHEET

Type no.	DA 72	
Article no.	013572090801	
Standards	DIN EN 50342-1,50342-2	
Application	Starter battery	
Electrical data		
Rated voltage	12V	
Rated capacity	72 Ah (K20)	
Cold start current	660 A (EN)	
Dimensions and weights		
Box	LB3	
Length max.	278mm	
Width max.	175mm	
Box height max.	175mm	
Total height max.	175mm	
Battery weight	Ca. 17,5 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	64	
Pallet ID	Euro pallet	
Items per layer	16	
Features		
Base hold-down	B13	
Layout	0	
Terminal	1	
Separator	PE bag separator	
Degassing	Battery with central degassing	
Flame arrester	Available	
Maintenance ¹⁾		
Water consumption	< 1g/Ah	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 3 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage ²⁾	max. 14,8 V	

Symbolpicture

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge

