

12 V 145 Ah (C₁₀) Deep Cycle AGM Battery

PHYSICAL CHARACTERISTICS

	SI Units	US Units
Length	513 mm	20.1 inch
Width	223 mm	8.7 inch
Height	223 mm	8.7 inch
Typical weight	47.3 kg	104.3 lbs



Specifications:

- Nominal voltage: 12 V
- Rated capacity: 145 Ah (at C₁₀)
- Separator: AGM
- Electrolyte: Sulphuric acid; analytical grade
- Self discharge: < 2.5% per month at 20°C
- Standards: IEC 61056; IEC 61427; IEC 60896
- Venting valve: One way, self resealing
- Degassing system: Central
- Terminal type: Top / Automotive
- Case / lid material: Polypropylene
- Carrying Handles: Available (2)

Performance characteristics:

BATTERY DISCHARGE PERFORMANCE AT 25°C

Discharge time	15 min	1 h	5 h	10 h	100 h
End of discharge voltage	9.60 V	9.60 V	10.20 V	10.80 V	10.80 V
Discharge capacity	70 Ah	100 Ah	130 Ah	145 Ah	170 Ah
Constant power discharge (per block)	3100 W	1100 W	300 W	170 W	20 W
Reserve capacity at 25 A	300 min / 125 Ah				

Temperature correction factor of discharge capacity

Temperature	-20 °C	-10 °C	0 °C	10 °C	20 °C	40 °C
Correction factor	0.50	0.70	0.83	0.91	0.97	1.04

BATTERY CHARGE CONDITIONS

Constant current charge	Current range: 0.1 – 0.2C ₁₀ A
Constant voltage charge	Voltage range: 14.10 – 15.10 V (Recommended: 14.40 V)
Float voltage	13.62 V (2.27 Vpc) at 20 °C
Temperature correction factor	Below 20 °C: + 0.018 V/block/°C; Above 20 °C: - 0.018 V/block/°C
Float application	Recommended: max. 0.1C ₁₀ A / 13.62 V (2.27 Vpc)
Cycle applications	Recommended: max. 0.2C ₁₀ A / 14.40 V (2.40 Vpc) Recharge Ah: at least 105% from previous discharge Ah

